



K



単位：mm

車輪径 D	型 式	車 輪 W	許容荷重	取付高 H	取付ピッチ P1×P2	プレート寸法 F1×F2	金具幅 B	取付穴径 d	軸径 A
75	75K A	ゴム	70kg	112.5	75 (2穴)	95×57	40	11	10
	75K B	ゴム (B入)							
	75K ULB	ウレタン (B入)	160kg						
	75K FA	鉄	140kg						
	75K FB	鉄 (B入)							
	75K MCB	MCナイロン (B入)	160kg						
100	100K A	ゴム	100kg	140	90 (2穴)	115×61	47	11	12
	100K B	ゴム (B入)	210kg						
	100K ULB	ウレタン (B入)	200kg						
	100K FA	鉄	210kg						
	100K FB	鉄 (B入)							
	100K MCB	MCナイロン (B入)	210kg						
125	125K A	ゴム	180kg	168.5	105×32	130×68	53	11	17
	125K B	ゴム (B入)	300kg						
	125K ULB	ウレタン (B入)	360kg						
	125K FA	鉄							
	125K FB	鉄 (B入)							
	125K MCB	MCナイロン (B入)	360kg						
150	150K A	ゴム	200kg	195	120×45	150×73	57	11	20
	150K B	ゴム (B入)	350kg						
	150K ULB	ウレタン (B入)	400kg						
	150K FA	鉄							
	150K FB	鉄 (B入)							
	150K MCB	MCナイロン (B入)	400kg						
180	180K A	ゴム	240kg	225	135×45	160×73	57	11	20
	180K B	ゴム (B入)	430kg						
	180K ULB	ウレタン (B入)	480kg						
	180K FA	鉄							
	180K FB	鉄 (B入)							
	180K MCB	MCナイロン (B入)	480kg						
200	200K A	ゴム	250kg	250	150×50	180×80	61	14	20
	200K B	ゴム (B入)	500kg						
	200K ULB	ウレタン (B入)							
	200K FA	鉄							
	200K FB	鉄 (B入)							
	200K MCB	MCナイロン (B入)	500kg						
230	230K A	ゴム	280kg	290	160×60	190×88	67	14	25
250	250K A	ゴム	340kg	300	160×60	190×88	67	14	25
	250K B	ゴム (B入)	650kg						
	250K ULB	ウレタン (B入)	680kg						
	250K FA	鉄							
	250K FB	鉄 (B入)							
	250K MCB	MCナイロン (B入)	680kg						
300	300K A	ゴム	360kg	350	175×60	206×92	71	14	25
	300K B	ゴム (B入)	830kg						
	300K ULB	ウレタン (B入)							
	300K FB	鉄 (B入)							
	300K MCB	MCナイロン (B入)	830kg						

caster

caster

lifter

carrier

special